

## Product datasheet

SSL-G2-80W

**LED street light 80 W**  
**3000 K, 4000 K ili 6500 K**

- Outdoor public lighting
- BRIDGELUX LED chip
- Provides safety for drivers and pedestrians
- High lumenation



## General information

|                         |  |
|-------------------------|--|
| • Model                 | SSL-G2-80W                               |
| • LED chip              | BRIDGELUX                                |
| • Body material         | Aluminium                                |
| • Environment           | Street light, parks, parking spaces, ... |
| • Product color         | Black                                    |
| • Operating Temperature | from - 20 °C to + 40 °C                  |
| • IP Protection Rate    | IP65                                     |
| • Weight                | 2,840 kg                                 |

## Electrical Specifications

|                          |                            |
|--------------------------|----------------------------|
| • Power Consumption      | 80 W                       |
| • Input Voltage          | AC 85 - 265 V / 50 - 60 Hz |
| • Dimmable Function      | No                         |
| • Replacing LED          | Yes                        |
| • Replacing Power Supply | Yes                        |

## Lighting Specifications

- |                            |                            |
|----------------------------|----------------------------|
| • Luminous flux            | 8000 lm                    |
| • Luminous efficiency      | 100 lm / W                 |
| • Color of the light       | Optional choice for buyers |
| • CCT                      | 3000 K, 4000 K or 6500 K   |
| • Color Render Index (CRI) | > 80                       |
| • Beam Angle               | 120 °                      |
| • Life Span                | 30 000 working hours       |

## Packing Information

- |                      |                    |
|----------------------|--------------------|
| • Package dimensions | 235 x 530 x 100 mm |
| • Gross Weight       | 4,240 kg           |
| • Transport package  | 1 piece            |

## Dimensions

- |                                |                   |
|--------------------------------|-------------------|
| • Product dimensions           | 220 x 520 x 65 mm |
| • Installation hole dimensions | 60 x 55 mm        |