

## Product datasheet

MPX-50-CW

**LED portable flood light  
50 W | 6000 K**

- Indoor and outdoor lighting
- SAMSUNG LED chip
- Without flickering
- Usable in all weather conditions



## General information

• Model	MPX-50-CW
• LED chip	SAMSUNG LED chip
• Body material	Aluminium
• Environment	Indoor and outdoor lighting
• Product color	Black + yellow
• Operating Temperature	from - 20 °C to + 45 °C
• IP Protection Rate	IP65
• Weight	1,390 kg

## Electrical Specifications

• Power Consumption	50 W
• Input Voltage	AC 220 - 240 V / 50 - 60 Hz
• Cable length	300 cm
• Dimmable Function	No
• Replacing LED	Yes
• Replacing Power Supply	Yes

## Lighting Specifications

• Luminous flux	6000 lm
• Luminous efficiency	120 lm / W
• Color of the light	Cold White
• CCT	6000 K
• Color Render Index (CRI)	70
• Beam Angle	120 °
• PF:	0.9
• Life Span	30 000 working hours

## Packing Information

• Package dimensions	280 x 290 x 65 mm
• Gross Weight	1,500 kg
• Transport package	6 pieces

Dimensions

- Product dimensions

277 x 286 x 45 mm

