

Product datasheet

WFS-50-CW

LED flood light with sensor 50 W | 6500 K

- Indoor and outdoor lighting
- Wide beam angle
- Without flickering
- Usable in all weather conditions



	1	
General	l informatio	n

• Model	WFS-50-CW
• LED chip	San`an
Body material	Aluminium
• Environment	Indoor and outdoor lighting
Product color	White
Operating Temperature	from - 20 °C to + 40 °C
Mounting	Surface mounting
• IP Protection Rate	IP65
• Weight	0,665 kg
Detection distance	10 m / work 10 sec - 10 min (adjustable)

Electrical Specifications

• Power Consumption	50 W
• Inpult Voltage	AC 176 - 265 V / 50 - 60 Hz
• Dimmable Function	No
Replacing LED	No
Replacing Power Supply	No

Lighting Specifications

• Luminous flux	4250 lm
• Luminous efficiency	85 lm / W
• Color of the light	Cold White
• CCT	6500 K
• Color Render Index (CRI)	≥ 80
Beam Angle	100°
• Life Span	30 000 working hours

Packing Information

 Package dimensions 	220 x 235 x 45 mm
Gross Weight	0,740 kg
Transport package	20 pieces

Dimensions

• Product dimensions

217 x 215 x 45 mm

